# TECHNICAL CHARACTERISTICS

| TREAD PATTERN AND DIMENSION | LOAD / SPEED INDEX | MAX LOAD ON STEER AXLE | RECOMMENDED RIM | 3PMSF M+S | TRACTION | EUROPEAN LABELLING | | |
|---|---|---|---|---|---|---|---|---|
| **LONG DISTANCE AND REGIONAL** | | | | | | | | |
| 295/80 R 22.5 MICHELIN X® COACH™ Z | 154/150M | 7,5 t | 8.25 x 22.5 | YES | YES | C | B | 71 dB |
| 295/80 R 22.5 MICHELIN X® COACH™ XD | 152/148M | - | 8.25 x 22.5 | YES | YES | E | C | 72 dB |
| 295/80 R 22.5 MICHELIN XZA 2 ENERGY™ | 152/148M | 7,1 t | 8.25 x 22.5 | - | - | C | C | 67 dB |
| 315/70 R 22.5 MICHELIN X® LINE™ ENERGY™ Z | 156/150L | 8 t | 9.00 x 22.5 | - | - | B | B | 69 dB |
| 315/70 R 22.5 MICHELIN X® LINE™ ENERGY™ D2 | 154/150L | - | 9.00 x 22.5 | YES | YES | A | B | 70 dB |
| 315/80 R 22.5 MICHELIN X® LINE™ ENERGY™ Z | 156/150L | 8 t | 9.00 x 22.5 | - | - | B | B | 69 dB |
| 315/80 R 22.5 MICHELIN X® LINE™ ENERGY™ D | 156/150L | - | 9.00 x 22.5 | YES | YES | B | C | 69 dB |
| 315/80 R 22.5 MICHELIN X® MULTIWAY™ 3D XZE | 156/150L | - | 9.00 x 22.5 | YES | YES | C | B | 72 dB |
| **INTERCITY** | | | | | | | | |
| 295/80 R 22.5 MICHELIN X® INCITY™ XZU 3+ TL | 152/148J | 7,1 t | 8.25 x 22.5 | YES | YES | D | C | 70 dB |
| 305/70 R 22.5 MICHELIN X® INCITY™ Z | 153/150J | 7,3 t | 8.25 x 22.5 | YES | YES | C | C | 69 dB |
| **EXTREME WINTER CONDITIONS** | | | | | | | | |
| 295/80 R 22.5 MICHELIN X® MULTI™ WINTER Z TL | 154/149L | 7,5 t | 8.25 x 22.5 | YES | YES | D | B | 73 dB |
| 295/80 R 22.5 XDW ICE GRIP TL | 152/149L | - | 8.25 x 22.5 | YES | YES | E | C | 72 dB |
| 315/80 R 22.5 XDW ICE GRIP TL | 156/150L | - | 9.00 x 22.5 | YES | YES | E | C | 72 dB |
| 315/80 R 22.5 XFN 2+ TL | 156/150L | 8 t | 9.00 x 22.5 | YES | - | D | C | 72 dB |

## NOMINAL INFLATION PRESSURE TABLE* (BAR)

| | | COACHES | | | | |
|---|---|---|---|---|---|---|
| | | 4 x 2 | | 6 x 2 | | |
| DIMENSIONS | LOAD / SPEED INDEX | FRONT | REAR S or D | FRONT | REAR S or D | REAR 2 |
| 295/80 R 22.5 | 152/148M | 8.50 | 8.00 | 8.50 | 8.00 | 8.00 |
| 295/80 R 22.5 | 154/150M | 8.50 | 8.00 | 8.50 | 8.00 | 8.00 |
| 305/70 R 22.5 | 153/150J | 9.00 | 8.00 | 9.00 | 8.00 | 8.00 |
| 315/70 R 22.5 | 156/150L | 8.50 | 8.00 | 8.50 | 8.00 | 8.00 |
| 315/70 R 22.5 | 154/150L | 8.50 | 8.00 | 8.50 | 8.00 | 8.00 |
| 315/80 R 22.5 | 156/150L | 8.50 | 8.00 | 8.50 | 8.00 | 8.00 |

*Values recommended by Michelin.

*FIND OUT MORE AND VISIT US ONLINE*

**WEBSITE**
trucks.michelin.com

**MYACCOUNT**
myaccount.michelin.eu

**YOUTUBE**
Michelin Trucks and Buses Tyres Europe

**LINKEDIN**
Michelin Trucks and Buses Tyres Europe

**TWITTER**
@MichelinTruckUK

MICHELIN

*GUARANTEE THE SAFETY OF YOUR DRIVERS AND PASSENGERS*

*OPTIMISE YOUR UPTIME*

MICHELIN

# A RANGE OF MICHELIN TYRES DESIGNED FOR ALL YOUR COACHES AND CONDITIONS OF USE

## LONG DISTANCE

| TYRE | ALL POSITION | DRIVE AXLE | BENEFITS |
|---|---|---|---|
| NEW X® COACH™ Z & XD 295/80 R 22.5 | 295/80 R 22.5 X® COACH™ Z | 295/80 R 22.5 X® COACH™ XD | Optimised load capacity of 7,5 t on the front axle. All-season mobility. Maximum comfort & safety. |
| | 295/80 R 22.5 XZA 2 ENERGY™ | 295/80 R 22.5 XZA 2 ENERGY™ | Optimised fuel consumption. |
| X® LINE™ ENERGY™ Z 315/70 R 22.5 & 315/80 R 22.5 | 315/70 R 22.5 X® LINE™ ENERGY™ Z | 315/70 R 22.5 X® LINE™ ENERGY™ Z | Load capacity of 8 t on the front axle. More room inside. Fuel savings thanks to a low rolling resistance. |
| | 315/80 R 22.5 X® LINE™ ENERGY™ Z | 315/80 R 22.5 X® LINE™ ENERGY™ Z | Load capacity of 8 t on the front axle. Fuel savings versus MICHELIN X® MULTIWAY™ 3D range. |

## REGIONAL (SCHOOLS AND COMPANIES)

| TYRE | ALL POSITION | DRIVE AXLE | BENEFITS |
|---|---|---|---|
| NEW X® COACH™ Z & XD 295/80 R 22.5 | 295/80 R 22.5 X® COACH™ Z | 295/80 R 22.5 X® COACH™ XD | Optimised load capacity of 7,5 t on the front axle. All-season mobility. Maximum comfort & safety. |
| X® MULTIWAY™ 3D XZE 315/80 R 22.5 | 315/80 R 22.5 X® MULTIWAY™ 3D XZE | 315/80 R 22.5 X® MULTIWAY™ 3D XZE | Load capacity of 8 t on the front axle. Mobility in all conditions, meeting current winter regulations. Easy management. |

## INTERCITY

| TYRE | ALL POSITION | DRIVE AXLE | BENEFITS |
|---|---|---|---|
| X® INCITY™ XZU 3+ 295/80 R 22.5 / X® INCITY™ Z 305/70 R 22.5 | 295/80 R 22.5 X® INCITY™ XZU 3+ | 295/80 R 22.5 X® INCITY™ XZU 3+ | Robust casing with reinforced sidewalls. All-season mobility. |
| | 305/70 R 22.5 X® INCITY™ Z | 305/70 R 22.5 X® INCITY™ Z | |

## EXTREME WINTER CONDITIONS

| TYRE | ALL POSITION | DRIVE AXLE | BENEFITS |
|---|---|---|---|
| X® MULTI™ WINTER Z 295/80 R 22.5 / XFN 2+ 315/80 R 22.5 | 295/80 R 22.5 X® MULTI™ WINTER Z | 295/80 R 22.5 X® MULTI™ WINTER Z | Increased mobility and safety in severe winter conditions. Load capacity of 7,5 t on the front axle. Easy management. |
| XDW ICE Grip 295/80 R 22.5 & 315/80 R 22.5 | 295/80 R 22.5 X® MULTI™ WINTER Z | 295/80 R 22.5 XDW ICE GRIP | Maximum mobility and traction in extreme winter conditions. Load capacity of 7,5 t on the front axle. |
| | 315/80 R 22.80 XFN2+ | 315/80 R 22.5 XDW ICE GRIP | Maximum mobility and traction in extreme winter conditions. Load capacity of 8 t on the front axle. |

## USE OUTSIDE EUROPE

Exports outside Europe require special attention to precisely meet the regulatory requirements in the destination country.

In order to best address your needs, the Michelin teams are available to establish the best tyre recommendations.

Don't hesitate to contact us!