

RIKEN

Just Efficient

APRIL 2018

ROAD READY



ON-OFF READY



URBAN READY



Visit us on riken.com

RIKEN

AFFORDABLE & SAFE

- > Extra wide shoulders
- > Reinforced steel belts
- > Regroovable and retreadable

PEACE OF MIND

- > Easy to fit
- > Reliable
- > Efficient torque transmission

100% EUROPEAN

- > Designed for the European conditions (M+S / 3PMSF)
- > Complying with regulations (EU labelling, REACH)
- > Made in Europe (ISO 9001 & 14001 certifications)

RIKEN ROAD READY

MEDIUM TRUCK
& LOW BED TRAILER
REGIONAL & LONG HAUL USE



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
205/75R17.5 Steer	124/122M		D	B	68 dB	M+S			1
215/75R17.5 Steer	126/124M		D	B	68 dB	M+S			1
235/75R17.5 Steer	132/130M		D	B	68 dB	M+S			1
245/70R17.5 Steer	136/134M		D	B	68 dB	M+S			1
265/70R19.5 Steer	140/138M		C	B	69 dB	M+S			1



TRAILER



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label			Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)				
215/75R17.5 Trailer	135/133J		D	B	69 dB	M+S		FRT	2
235/75R17.5 Trailer	143/141J	144F	C	B	69 dB	M+S		FRT	2
245/70R17.5 Trailer	143/141J	144F	C	B	69 dB	M+S		FRT	2
265/70R19.5 Trailer	143/141J		C	B	69 dB	M+S		FRT	2

REGROOVING

● Recommended position ● Possible position


Reference	1	2	
Blade	R3	R3	
Width	6 to 8 mm	6 to 8 mm	
Max Depth	2 mm	2 mm	

**RIKEN
ROAD
READY**

**HEAVY TRUCK
REGIONAL & LONG HAUL USE**



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)					
295/80R22.5 Steer	152/148M		C	C	70 dB		M+S			3
315/80R22.5 Steer	156/150L		C	B	70 dB		M+S			3
315/70R22.5 Steer	154/150L		C	C	72 dB		M+S			3
385/65R22.5 Steer	160K	158L	C	B	72 dB		M+S			3



DRIVE



FITTING DIRECTION⁽⁴⁾

Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)					
295/80R22.5 Drive	152/148M		C	C	73 dB		M+S		Traction	4
315/80R22.5 Drive	156/150L		C	C	73 dB		M+S		Traction	4
315/70R22.5 Drive	154/150L		C	C	73dB		M+S		Traction	4



TRAILER



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
			(1)	(2)	(3)					
385/65R22.5 Trailer	160K		C	C	70 dB		M+S		FRT ⁽⁵⁾	5

● Recommended position ● Possible position

REGROOVING

Reference	3	4	5
Blade	R3	R3	R4
Width	7 to 8 mm	7 to 8 mm	7 to 8 mm
Max Depth	2 mm	2 mm	2 mm


RIKEN

**RIKEN
URBAN
READY**

URBAN BUS



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
										
275/70R22.5 Steer	150/148J		D	B	71 dB		M+S			6

**RIKEN
ON-OFF
READY**

HEAVY TRUCK
ON-OFF USE



STEER / ALL POSITION



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
										
315/80R22.5 Steer*	156/150K		C	B	71 dB		M+S			7
13R22.5 Steer	156/150K		D	B	69 dB		M+S			7
385/65R22.5 Steer**	160K	158L	C	C	72 dB		M+S			7




DRIVE



Size & Tread Position	Load & Speed Index	Unique Point	EU Tyre Label				Winter Marking		Other Marking	Regrooving Reference
										
315/80R22.5 Drive	156/150K		D	B	75 dB		M+S		Traction	8
13R22.5 Drive	156/150K		D	B	74 dB		M+S		Traction	8

● Recommended position ● Possible position

REGROOVING

			
Reference	6	7	8
Blade	R3	R4	R3
Width	10 mm	10 mm	10 mm
Max Depth	2 mm	2 mm	2 mm

All tyres are compliant with UNECE/R54 and ETRTO standards - (1) Fuel efficiency (from A to G) - (2) Wet grip (from A to G) - (3) External rolling noise class (from 1 to 3) & External rolling noise measured value (decibel).



More information on riken.com