

MICHELIN X[®] MULTI[™] Z

**IMPROVED LONGEVITY*
AND MOBILITY IN ALL
CLIMATIC CONDITIONS**



CUT OPERATING COSTS:

• **AT LEAST +20% MILEAGE***



DESIGNED FOR NATIONAL
AND REGIONAL OPERATIONS
ON ALL TYPES OF ROADS



**ALL POSITIONS
MAINLY FOR
STEER AXLE**

385/65 R 22.5



3PMSF

M+S



+20% for the MICHELIN 385/65 R 22.5 X MULTI Z vs. MICHELIN 385/65 R 22.5 X MULTI F : internal test made in real conditions in Spain in 2018 (tractor unit fitted with MICHELIN 385/65 R 22.5 X MULTI Z compared to tractor unit fitted with MICHELIN 385/65 R 22.5 X MULTI F).



MICHELIN

MICHELIN X® MULTI™ Z



BUSINESS EFFICIENCY

REDUCE YOUR OPERATING COSTS

■ Lower cost per mile

- At least 20% increased mileage potential*

- New generation of tread rubber mix that enables a reduction in original tread depth without affecting mileage performance
- Regenion, Forcion and Infinicoil technologies

■ Suitable for all road surfaces



SAFETY

ALWAYS TRANSPORT SAFELY WHATEVER THE WEATHER CONDITION

■ High level of grip throughout the tyres lifetime

- 3PMSE and M+S marking


- New generation of blend of rubber mix
- Regenion technology



ECOLOGY

A GREENER WAY TO TRANSPORT GOODS

- Retreading and regrooving save materials and fuel
- Tyres manufactured in compliance with ISO 14001 environmental standards



CASING

POWERCOIL TECHNOLOGY: CASING ROBUSTNESS AND MILEAGE


- New generation of more robust steel cables
- Better oxidation resistance
- Enhanced casing endurance



COMPOUND

FORCION TECHNOLOGY SPECIAL MIXTURES: MILEAGE

- New material resulting from an innovative agent
- Enhanced rubber reinforcement
- More cohesive compound
- Increased mileage performance
- Greater resistance against abrasions, cuts and chips



TREAD PATTERN

REGENION TECHNOLOGY: WET AND WINTER GRIP

- Self-regenerating tread blocks, supported by MICHELIN mold 3D metal printing technologies
- Solid grip throughout the tyre's lifetime and conditions
- New grooves emerge over the tyre's life
- Enhanced mobility



CASING

HIDDEN GROOVES: MORE GRIP

- Small holes (the volcanos) appear and allow the longitudinal rain drop sipes to be used earlier.
- Volcanos make the hidden volume accessible to water before the new grooves emerge.
- For sustainable Grip


TECHNICAL INFORMATION

EUROPEAN LABELLING

TREAD PATTERN AND DIMENSION	TYPE	LOAD/SPEED INDEX	MICHELIN PREFERRED RIM	ORIGINAL TREAD DEPTH	SPECIAL MARKINGS	RADIO FREQUENCY IDENTIFICATION CHIP INTEGRATED	Rolling noise (dB)	Rolling noise (dB)	Rolling noise (dB)
385/65 R 22.5 MICHELIN X® MULTI™ Z	TL	160K SP : 158L	11.75	13.5 mm	M+S Traction	RFID	B	B	71 dB

REGROOVING INFORMATION

TREAD PATTERN AND DIMENSION	THEORETICAL REGROOVING DEPTH	SUGGESTED BLADE
385/65 R 22.5 MICHELIN X® MULTI™ Z	3 mm	R3



Regroovable and retreadable **MICHELIN** ➔ **REMIX** on drive axle for 315/60 R 22.5 and 315/70 R 22.5, and on trailer axle for 385/65 R 22.5.

MICHELIN products are manufactured from high quality materials to high tolerances, ensuring a uniform and consistent performance. Correct application, fitting, inflation and regular inspection of the product are essential to its safe and efficient operation. Remix and the tyre designations mentioned are trademarks of Michelin. For further information about any of the products in this document, contact your local Michelin representative.
+20% for the MICHELIN 385/65 R 22.5 X MULTI Z vs. MICHELIN 385/65 R 22.5 X MULTI F : internal test made in real conditions in Spain in 2018 (tractor unit fitted with MICHELIN 385/65 R 22.5 X MULTI Z compared to tractor unit fitted with MICHELIN 385/65 R 22.5 X MULTI F).

