



**MICHELIN**  
*Pilot Street*



**BOOST YOUR RIDING PLEASURE**

**+ WHY IS THE DIRECTION OF ROTATION OF THE FRONT AND REAR TYRES DIFFERENT ?**

Front and rear tyres have virtually opposite demands placed on them, in that the front tyre has to withstand heavy braking forces, and the rear tyre has to withstand hard acceleration forces. Tread pattern designs must take these forces into account in order to perform well and wear evenly. Careful design of our tyres has enabled us to design a tread pattern that is adapted to these differing demands by simply reversing the direction of rotation.

For more information contact the 2 Wheel Technical department on 0845 366 1589.

**IN BRIEF**

- › FOR EVERYDAY USE, RELIABLE EVEN ON WET ROADS.
- › LASTS 35% LONGER THAN THE MICHELIN PILOT SPORTY\*
- › EXCELLENT HANDLING FOR EVERYDAY RIDING PLEASURE
- › DESIGN INSPIRED BY MICHELIN SPORT TOURING MOTORCYCLE TYRES

**OFFER THE BEST BALANCE BETWEEN GRIP AND DURABILITY**

The grooves that run from the centre to the shoulder improve water clearance for dependable wet grip.



**FRONT**

Width	Ratio	Diam.	Load index	Speed index	Std / reinf.	TL / TT	CAI	In. Tube
90	80	17	46	S	-	TL/TT	191781	17ME
90	90	17	49	P	-	TL	327126	-
100	80	17	52	S	-	TL/TT	510280	17ME
110	70	17	54	S	-	TL/TT	393922	17MG
110	70	17	54	H	-	TL/TT	627009	17MG
2.75	-	18	42	P	-	TL/TT	342827	18ME

**REAR**

Width	Ratio	Diam.	Load index	Speed index	Std / reinf.	TL / TT	CAI	In. Tube
80	100	14	49	L	Reinf	TT	417470	14MCG
120	80	17	61	P	-	TL	298553	-
130	70	17	62	S	-	TL	758449	17MH
140	70	17	66	S	-	TL/TT	024137	17MH
140	70	17	66	H	-	TL/TT	666756	17MH
90	90	18	57	P	Reinf	TL/TT	898552	18ME
100	90	18	56	P	-	TL/TT	391925	18ME

**FRONT / REAR**

Width	Ratio	Diam.	Load index	Speed index	Std / reinf.	TL / TT	CAI	In. Tube
70	90	14	40	P	Reinf	TL/TT	277463	-
80	80	14	43	P	Reinf	TL	320632	-
80	90	14	46	P	Reinf	TL/TT	902535	14MCG
90	80	14	49	P	Reinf		256067	-
90	90	14	52	p	Reinf	TL/TT	582269	-
100	90	14	57	p	-	TL/TT	944867	-
110	80	14	59	P	Reinf	TL	919818	-
120	70	14	61	P	Reinf	TL	696105	-
80	90	16	48	S	Reinf	TL/TT	749130	-
60	90	17	30	S	-	TT	372991	-
60	100	17	33	L	-	TL/TT	810954	-
70	90	17	38	S	-	TT	654098	-
70	90	17	43	S	Reinf	TL/TT	788900	-
2.50	-	17	43	P	Reinf	TT	517102	17MC
80	80	17	46	P	Reinf	TL	701696	-
80	90	17	50	S	Reinf	TL/TT	446544	-
100	70	17	49	S	-	TL/TT	765043	-
100	80	17	48	p	-	TL/TT	20016	-
110	80	17	57	S	-	TL/TT	010712	17ME
120	70	17	58	S	-	TL	744651	-

\* According to external independent longevity tests conducted by the MAUA Institute in Brazil in 2011.